

Key information:

- Comfortable and dexterous 15g Recycled Polyester/Metal Q/ Spandex Liner
- Black Sandy Nitrile Foam Palm Coating
- Additional Nitrile Thumb Crotch Protection
- Touchscreen Compatible

- Contact Heat Level 1
- Cut Level E
- Elasticated, coloured cuff for size indication
- Fibre Composition, 17% rPET, 49% Metal Q, 2% Spandex, 32% Nitrile









Code: RPET15E

Liner: 15g rPET/Metal Q/Spandex

Size: 6 to 11

Pack size: 10 pairs

Carton: 120 pairs EN388: 4X43E

EN407: X1XXXX



Applications include:

Engineering, Construction, Assembly, Agriculture, Glass Handling, Fabrication

Limitations of Use

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.

Storage Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

Disposal Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

Cleaning Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.

Durability The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.

Note Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.



Hands Protected; Work Perfected